

## DECLARATION OF PERFORMANCE

**No. LE\_089285331\_00\_M\_Neutralsilikon A8 PRO**

**This is an English translation of the original German wording.  
In cases of doubt, the German version applies**

1. Unique identification code of the product type: Neutralsilikon A8 PRO  
(neutral silicone A8 PRO)  
Article no.: 089285331; 089285332; 0892853372; 0892853371;  
0892853322; 0892853324; 0892853351; 0892853315; 0892853313;  
089285361; 089285362
2. Intended use(s): F-EXT-INT (EN 15651-1) joint sealants for facade elements for indoors and outdoors  
G-CC (EN 15651-2) joint sealants for glazing  
PW-EXT-INT-CC (EN 15651-4) sealant for floor joints
3. Manufactured by: Adolf Würth GmbH & Co. KG  
Reinhold-Würth-Str. 12 - 17  
D-74653 Künzelsau
4. System(s) of assessment and verification of constancy of performance: System 3
5. Harmonised standard: EN 15651-1:-/2:-/4: 2012  
Notified Body or Bodies: 1213, SKZ - SKZ - Testing GmbH
6. Declared performance:

| Essential characteristics                                                                                     | Performance | Harmonized technical specification                       |
|---------------------------------------------------------------------------------------------------------------|-------------|----------------------------------------------------------|
| Fire behavior                                                                                                 | Class E     | EN 15651-1: 2012<br>EN 15651-2: 2012<br>EN 15651-4: 2012 |
| Release of chemicals harmful to health and/or the environment.<br>Volatile organic compounds (VOC) contents:  | < 0.1%      |                                                          |
| Loss in volume                                                                                                | ≤ 10%       |                                                          |
| Tensile strength at -30 °C (ISO 8339)                                                                         | ≤ 0.9 MPa   |                                                          |
| Durability                                                                                                    | Passed      |                                                          |
| Tensile properties at maintained extension (ISO 8340)                                                         | Passed      |                                                          |
| Tensile properties (i.e. cohesion properties) at maintained extension and with immersion in water (ISO 10590) | Passed      | EN 15651-1: 2012<br>EN 15651-4: 2012                     |
| Resistance to flow (ISO 7390)                                                                                 | ≤ 2 mm      | EN 15651-1: 2012<br>EN 15651-2: 2012                     |
| Elastic recovery (ISO 7389)                                                                                   | ≥ 70%       | EN 15651-2: 2012                                         |
| Resistance to tearing (EN ISO 8340)                                                                           | ≤ 12 mm     | EN 15651-4: 2012                                         |
| Tensile properties secant modulus at 23 °C (ISO 8339)                                                         | ≤ 0.4 MPa   |                                                          |
| Compressive strength (ISO 11432)                                                                              | Passed      | EN 15651-2: 2012                                         |

The performance of the above product corresponds to the declared performance. The declaration of performance is issued in compliance with EU Regulation 305/2011 under the sole responsibility of the above manufacturer.

Signed for and on behalf of the manufacturer by:



---

Frank Wolpert  
Authorized Signatory, Head of Product  
Management

Künzelsau, 1/9/2020

Checklist

Checked by:

Andreas Perschin ☒

Signed by:

Frank Wolpert ☐

Siegfried Beichter ☐



---

Dr.-Ing. Siegfried Beichter  
Head of Quality, Authorized Signatory